This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:
G06K 17/00
A1
(11) International Publication Number: WO 00/65532
(43) International Publication Date: 2 November 2000 (02.11.00)

(21) International Application Number: PCT/US00/11304

(22) International Filing Date: 27 April 2000 (27.04.00)

(30) Priority Data:
99303314.1
28 April 1999 (28.04.99)
EP

(71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventor; and


(75) Inventor/Applicant (for US only): ASHTON, Kevin, John [GB/GB]; 8 St. Giles Road, London SE5 7RL (GB).

(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US). (81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: STORAGE SYSTEM



(57) Abstract

A storage system has one or more supports, for example, shelves (1) and, one or more sensors (3) which are arranged to detect the presence of transponders (6) associated with items (7) to be stored on the shelves. Information can thus be from the transponders, and transmitted to, for example, a data processing unit.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	· Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of Americ
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
2 CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL ·	Poland		
CN	China	KR	Republic of Korea	· PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	. SG	Singapore		

1

STORAGE SYSTEM

The present invention relates to storage systems and, more particularly, to storage systems of the type used to display items in a supermarket or the like. The term 'storage' is thus used in the context of the present application to mean a system on or in which items may be held temporarily or semi-permanently until moved therefrom, such as display shelving systems in retail outlets and the like, warehouse shelving, etc.

A number of difficulties exist in factories, wholesale outlets, and retail outlets such as supermarkets, in maintaining a stock of items and displaying items for sale to shoppers, etc. In particular in a retail outlet, it is necessary for the stocking of items on the shelves and similar supports to be monitored and, conventionally, this involves personnel carrying out a visual check and/or count in order to ensure that items are always available for purchase. However, this is obviously both time-consuming, prone to error, and expensive in staff costs. Additionally, changes in the pricing of items have to be indicated on the shelf and this again requires staff intervention. In both of these processes, monitoring and price adjustment, mistakes by staff can cause considerable annoyance and additional work.

The present invention is aimed at applying a system which can be used to overcome these problems as well as create additional advantages.

According to the present invention there is provided a storage system comprising one or more supports and, associated with the supports, one or more sensors arranged to detect the presence of transponders associated with items to be stored on the supports, to read information from the transponders, and to transmit information read from the transponders to, for example, a data processing unit.

The storage system may be a shelving system, for example, a display system as used in retail outlets or the like, or in warehouses etc.

An inventory control system may include a storage system as defined above, together with a data processing unit arranged to receive information the sensor or sensors.

The data processing unit is preferably a computer system programmed to maintain a database of information about individual items for stock control purposes and the like.

In particular, the transponders may comprise RFID or multi-bit magnetic tags which may be attached to or otherwise integrally associated with items to be stored and

displayed on the shelves.

By using such a system it is possible to detect or infer the presence, absence and removal of items from a support, eg. a shelf, either in real time or close to real time via continuous or continual intermittent polling.

2

The system may be used in a number of ways to manage logistics and inventory of items, for example, to analyse the level of stock of items on individual supports such as shelves and, via a computer system, trigger replenishment when the number of items falls below a pre-determined threshold level. The supports may be provided with electronic displays so as to display the prices of items and other information if desired, enabling price changes to be indicated substantially instantaneously. The location and quantity of items can also be checked for compliance with agreed plans and designs and misplaced items may also be readily located by means of such a system.

Accurate data about the off-take of items, for example, how many times an item is picked up and replaced before purchase, the effects of changes in store environment, e.g. signage, position, etc., and the identification of unusual shelf activity, e.g. the removal of large volumes of generally slow-moving items, may all be provided by such a system.

A number of examples of systems according to the present invention will now be described with reference to the accompanying drawings in which Figs. 1 to 5 each provide a diagrammatic cross-sectional view of a storage system in the form of a shelving system intended for reading radio frequency ID tags (RFID tags) which may be attached to or embedded in the packaging of individual items displayed for sale.

Fig. 1 illustrates a basic example in which a shelf 1 is supported from a wall panel or the like 2 along its rear edge, the shelf carrying, along its length, one or more antennas 3 which are shielded by appropriate shielding 4 from the shelf below and which, in effect, provide an antenna field 5 for the location and reading of information on RFID tags 6 attached to or embedded within items 7 disposed on the shelf 1. The RFID tags (which are conventional) each consist of an integrated circuit attached to a radio antenna affixed to substrate, and the shelf can send and receive digital data to the receiving antennae of the tags via radio signals at frequencies of the electro-magnetic spectrum including 125khz, 13.56mhz and 2.45ghz.

The or each antenna 3 is connected via a suitable cable 8 or else via wireless transmission to a computerized inventory control system which maintains a database which is updated by information supplied from the RFID tags 6 via the antennas 3.

Fig. 2 illustrates a modified design in which items 7 are intended to be slung beneath a shelf 1 which includes a hook or similar device to hold the items. Again, appropriate shielding can be provided for the antenna 3.

More complex designs may be necessary where items are intended for stacking one on top of another, because individual items may act as shields for the tag reading system by attenuating the radiation, so as to cause some tags to be unread. A more complex design is shown in Fig. 3 in which a pair of antennas are provided, one on the underside of an upper shelf 1 and another on the top of a lower shelf 1'.

Still more complex designs, such as that shown in Fig. 4 may be provided where multiple items may be stacked on top of one another, in this case, a further antenna 3 being disposed adjacent to the wall panel 2 or the like. Each of the antennas shown in Fig. 4 is disposed to detect a different set of tags depending upon the range and interference from the items themselves. Depending upon the information supplied by each tag, the computer system to which the antennas are attached will be able to identify or at least infer the number of products on the shelf.

An alternative approach indicated in Fig. 5, is the use of shelf antennas that can detect at different frequencies or different field sizes indicated by the different antenna fields 5, 5'. The system may be used in combination with a further antenna 3 located, for example, as shown, in an opposing shelf.

It will be readily apparent that a very wide number of possible configurations is available, depending upon the type of tags used, the items intended to be displayed, etc., and the present invention is not limited to any particular combination.

A system of this type is capable of providing monitoring and tracking of items in real time or close to real time with a high degree of accuracy and precision without the need for manual intervention. This overcomes the currently labour-intensive shelf checking systems presently used and enables a number of problems to be overcome such as misplacement of items, failure to replenish removed of items with sufficient speed, non-detection of shelf "sweeping" by thieves, failure to reorder stolen or shrunken stock and the need to conduct laborious stock checks on a regular basis.

Additionally, the tags may be read by appropriate checkout systems also connected to the computerized inventory system, providing additional information and verification.

CLAIMS


- 1. A storage system comprising one or more supports and, associated with the supports, one or more sensors arranged to detect the presence of transponders associated with items to be stored on the supports, to read information from the transponders, and to transmit information read from the transponders to, for example, a data processing unit.
- 2. A storage system according to claim 1, wherein at least one sensor is arranged to receive signals from a transponder comprising an RFID tag.
- 3. A storage system according to claim 1, wherein at least one sensor is arranged to receive signals from a transponder comprising a multi-bit magnetic tag.
- 4. A storage system according to any of claims 1 to 3, wherein one or more of the supports includes an electronic character display.
- 5. A storage system according to any of the preceding claims, wherein the supports comprise shelves.
- 6. An inventory control system including a storage system according to any of claims 1 to 5, and a data processing unit arranged to receive information the sensor or sensors.
- 7. An inventory control system according to claim 6, wherein the data processing unit is a computer system programmed to maintain a database of information about individual items held on the supports for stock control purposes and the like.
- 8. An inventory control system according to claim 6 or claim 7, including software to analyse the level of stock of items on individual shelves and provide a signal indicative of the requirement for replenishment of the items when the number of items falls below a pre-determined threshold level.
- 9. A system according to any of claims 6 to 8, when dependent on claim 5,

WO 00/65532 PCT/US00/11304


including means for passing information to a shelf display so as to display the prices of shelved items and/or other information, enabling price changes to be indicated substantially instantaneously when changes are made in the data processing unit.

5


- 10. A system according to any of claims 6 to 9, including means for checking the location and/or quantity of items at a given shelf location and providing an indication of misplaced items.
- 11. A system according to any of claims 6 to 10, including means for providing an indication of the removal of large numbers of items usually sold singly or in small numbers from a shelf location.




SUBSTITUTE SHEET (RULE 26)




SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)



INTERNATIONAL SEARCH REPORT

Intens onal Application No PCT/US 00/11304

A. CLASSI IPC 7	FICATION OF SUBJECT MATTER G06K17/00	,		
According to	o International Patent Classification (IPC) or to both national classific	ation and IPC		
	SEARCHED currentation searched (classification system followed by classification)	ina sumbole)		
IPC 7	G06K			
Documentat	tion searched other than minimum documentation to the extent that s	such documents are included in the fields se	arched	
Electronic d	ata base consulted during the international search (name of data ba	use and, where practical, search terms used	,	
EPO-In	ternal, WPI Data, PAJ, IBM-TDB, INS	PEC		
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the rei	levant passages	Relevant to claim No.	
X	WO 97 39398 A (ELDAT COMMUNICATION 23 October 1997 (1997-10-23) the whole document	ON LTD)	1-11	
X	WO 99 05660 A (CHECKPOINT SYSTEMS	1-3,6-8,		
,	4 February 1999 (1999-02-04)	10.	10,11	
Y	column 14, line 3 -column 44, lin figures 1-12	4,5,9		
Y	US 5 548 282 A (ESCRITT CHRIS ET 20 August 1996 (1996-08-20) column 7, line 26 -column 10, lin figures 1-18	4,5,9		
Funt	her documents are listed in the continuation of box C.	Patent family members are listed	in annex.	
"A" docume	tegories of cited documents: ent defining the general state of the art which is not	"T" later document published after the inte or priority date and not in conflict with cited to understand the principle or the	the application but	
"E" earlier o	lered to be of particular relevance document but published on or after the international	invention "X" document of particular relevance; the c		
which	late nt which may throw doubts on priority claim(s) or is cited to establish the publication date of another n or other special reason (as specified)	cannot be considered novel or cannot involve an inventive step when the do "Y" document of particular relevance; the cannot be considered to involve an inv	cument is taken alone laimed invention	
other		document is combined with one or mo ments, such combination being obvious	re other such docu-	
	ent published prior to the international filing date but and the priority date daimed	in the art. "&" document member of the same patent	family	
Date of the	actual completion of the international search	Date of mailing of the international sea	rch report	
1	1 July 2000	18/07/2000		
Name and n	nailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer		
	NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fax: (-31-70) 340-3016	Degraeve, A		

1

INTERNATIONAL SEARCH REPORT

information on patent family members

Inte ional Application No PCT/US 00/11304

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9739398	Α	23-10-1997	AU EP	2175997 A 0954806 A	07-11-1997 10-11-1999
WO 9905660	A	04-02-1999	US AU EP	5963134 A 8486598 A 0996941 A	05-10-1999 16-02-1999 03-05-2000
US 5548282	A	20-08-1996	AT AU AU DE EP JP	171553 T 666263 B 6182594 A 59406948 D 0623873 A 7143042 A	15-10-1998 01-02-1996 10-11-1994 29-10-1998 09-11-1994 02-06-1995